

## WAZZLE – Technical features

Standard sizes					
		Compact	Medium	Rarge	Extra Large
Capacity	10 m <sup>3</sup>		16 m <sup>3</sup>	30 m <sup>3</sup>	40 m <sup>3</sup>
Internal dim (WxDxH)	1820x2120x2560 mm	3000x2120x2560 mm	3640x3300x2560	4820x3300x2560	

COOLING UNITS (installed on the back)	CORRESPONDING AIR TREATMENT UNITS (installed on the ceiling)
1. A1 cooling unit (T range: -40°C/+80°C) 2. A2 cooling unit (T range: -70°C/+80°C) dim: 1550x1000x2180 mm (WxDxH)	Air treatment unit dim: 1650x700x560 mm (WxDxH)
3. B1 cooling unit (T range: -40°C/+80°C) 4. B2 cooling unit (T range: -70°C/+80°C) dim: 2000 x 1200 x 2180 mm (WxDxH)	Air treatment unit dim: 2050x700x560 mm (WxDxH)
5. C1 cooling unit (T range: -40°C/+80°C) 6. C2 cooling unit (T range: -70°C/+80°C) dim: 2000 x 1200 x 2180 mm (WxDxH)	Air treatment unit dim: 2750x700x560 mm (WxDxH)

## Temperature range and Rates\*

		Size							
		Compact	Medium	Rarge	Extra Large				
Cooling Units	A1	2.7▲	1.1▼	2.0▲	0.8▼	1.2▲	0.5▼	1.0▲	0.4▼
	B1	5.2▲	1.9▼	3.8▲	1.4▼	2.5▲	0.9▼	2.1▲	0.8▼
	C1	X**		7.4▲	2.0▼	3.7▲	1.4▼	3.0▲	1.2▼
	A2	2.7▲	1.5▼	5.5▲	1.1▼	1.2▲	0.7▼	1.0▲	0.5▼
	B2	5.2▲	2.6▼	2.0▲	1.9▼	2.5▲	1.3▼	2.1▲	1.0▼
	C2	X**		5.5▲	2.8▼	3.7▲	1.9▼	3.0▲	1.6▼

### Notes:

\* Temperature variation rates (°C/min) heating/cooling calculated in the temperature range -30°C/+80°C at empty chamber according to IEC 60068-3-5.

▲ Heating Up

▼ Cooling Down

 temperature range +80°C/-30°C
 
 temperature range +80°C/-40°C
 
 temperature range +80°C/-65°C
 
 temperature range +80°C/-70°C
 

\*\*the air treatment system is too big to be installed inside the chamber