

## Thermal Shocks technical characteristics

			Model								
			<b>CST27</b> <b>2T</b>	<b>CST84</b> <b>2T</b>	<b>CST157</b> <b>2T</b>	<b>CST320</b> <b>2T</b>	<b>CST500</b> <b>2T</b>	<b>CST1000</b> <b>2T</b>	<b>CSTL12</b>	<b>CSTL20</b>	<b>CSTL30</b>
<b>F</b> <b>e</b> <b>a</b> <b>t</b> <b>u</b> <b>r</b> <b>e</b> <b>s</b>	Basket dimensions (mm)	W	300	460	530	700	630	730	120	200	300
		D	300	460	660	700	900	1000	120	200	300
		H	300	400	450	650	900	1400	120	200	300
	External dimensions (mm)	W	970	1300	1360	1530	3830	4000**	1160	1400	3680
		D	2050	2560	2800	2900	2060	2200**	1050	1300	1200
		H	1750	2000	2050	2390	2640	2650	1900	2130	2170
Thermal Load(Kg)*		2.5/0.5	5.0/2.5	10/4.0	15/7.0	25.0/13.0	50.0/30.0	1.5/0.8	2.5/1.5	5.0/3.5	
Power (KW) Max		16	20	30	40	48	65	6	10	31	

\*Reference values for the acquisition of the following recovery times:

2 minutes (6 minutes for the CST1000) in the -55°C/+125°C range;

5 minutes (11 minutes for the CST1000) in the -55°C/+160°C range.

\*\* 4490x2420x2650 (including ventilation motors) (WxDxH)